

| Technical Data | A3 Sportback 35 TFSI S tronic 110 kW (MHEV) |
|--|--|
| Program for Germany | Status: 03/25/2020 |
| Engine / electrics | |
| Engine type | Inline 4-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1498 / 74.5 x 85.9 / 10.5 |
| Max. power output in kW (PS) / rpm | 110 (150) / 5000 - 6000 |
| Max. torque in Nm (lb-ft) / at rpm | 250 (184.4) / 1500 - 3500 |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter |
| Emissions standard | EU6 |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 320 / 59 |
| Max. electrical output at 12V in kilowatts | 3 |
| On-board voltage 1 in volts | 12 |
| On-board voltage 2 in volts | 48 |
| Drivetrain / transmission | |
| Drive type | Front-wheel drive |
| Clutch | Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel |
| Transmission type | 7-speed S tronic / dual clutch |
| Final drive ratio 1 to 2 | 4.8 |
| Final drive ratio 2 to 3 | 3.429 |
| Transmission ratio in 1st/2nd gear | 3.500 / 2.087 |
| Transmission ratio in 3rd/4th gear | 1.343 / 0.933 |
| Transmission ratio in 5th/6th gear | 0.974 / 0.778 |
| Transmission ratio in 7th/8th gear | 0.653 / - |
| Transmission ratio reverse gear | 3.722 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | Four-link rear suspension |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio | 14.9 |
| Turning circle in m (ft) | 11.1 (36.4) |
| Brake control system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist |
| Tires (basic) | 205/55 R 16 91 V |
| Wheels (basic) | Steel 7.0J x 16" |
| Consumption / emissions* | |
| Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (US mpg) | 6.2 - 6.0 (37.9-39.2) / 4.3 - 4.0 (54.7-58.8) / 5.0-4.7 (47.0-50.0) |
| CO ₂ emissions combined in grams per kilometer (g/mi) | 115-109 (185.1-175.4) |

| | |
|--|--|
| Performance / acoustics | |
| Top speed in km/h (<i>mph</i>) | 224 (139.2) |
| Limited | no |
| Acceleration, 0-100 km/h (0-62.1 <i>mph</i>) | 8.4 |
| Fuel type / octane value | Gasoline / 95 |
| Fuel standard | DIN EN 228 (gasoline) |
| Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A) | 75.0 / - / 68 |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 <i>mi</i>) / 2 years, whichever comes first |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 14 / 20 / 21 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1320 (2910.1) / 1395 (3075.4) / 1870 (4122.6) |
| Front/rear axle load limit in kg (<i>lb</i>) | 995 (2193.6) / 965 (2127.5) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1700 (3747.9) / 1500 (3306.9) // 690 (1521.2) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 (165.3) / 80 (176.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 11.2 (3.0) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 4.3 (4.5) |
| Fuel tank capacity in liters (<i>US gal</i>) | 50 (13.2) |
| Dimensions / body | |
| Body type / number of doors | Unitary steel / 5 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.29 / 2.17 (23.4) |
| Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (<i>ft</i>) | 4343 (14.2) / 1816 (6.0) / 1449 (4.8) |
| Width including mirrors in mm (<i>ft</i>) | 1984 (6.5) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2636 (8.6) / 1554 (5.1) / 1525 (5.0) |
| Height of loading edge with steel springs in mm (<i>ft</i>) | 671 (2.2) |
| Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1200 (42.4) |
| Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>) | 380 (13.4) |

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

| Technical Data | Audi A3 Sportback 35 TFSI (110 kW) |
|---|--|
| Program for Germany | Status: 03/05/2020 |
| Engine / electrics | |
| Engine type | Inline 4-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1498 / 74.5 x 85.9 / 10.5 |
| Max. power output in kW (PS) / rpm | 110 (150) / 5000 - 6000 |
| Max. torque in Nm (lb-ft) / at rpm | 250 (184.4) / 1500 - 3500 |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter |
| Emissions standard | Euro 6d-TEMP-EVAP-ISC |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 320 / 59 |
| Max. electrical output at 12V in kilowatts | 1.6 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | |
| Drive type | Front-wheel drive |
| Clutch | Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel |
| Transmission type | 6-speed manual transmission / manual |
| Final drive ratio 1 to 2 | 3.684 |
| Final drive ratio 2 to 3 | 3.684 |
| Transmission ratio in 1st/2nd gear | 3.750 / 1.952 |
| Transmission ratio in 3rd/4th gear | 1.200 / 0.925 |
| Transmission ratio in 5th/6th gear | 0.767 / 0.652 |
| Transmission ratio reverse gear | 3.583 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | Four-link rear suspension |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio | 14.9 |
| Turning circle in m (ft) | 11.1 (36.4) |
| Brake control system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist |
| Basic tires | 205/55 R 16 91 V |
| Wheels | Steel 7.0Jx16" |

| | |
|--|---|
| Performance / acoustics | |
| Top speed in km/h (<i>mph</i>) | 224 (139.2) |
| Limited | no |
| Acceleration, 0-100 km/h (0-62.1 <i>mph</i>) | 8.4 |
| Fuel type / octane value | Gasoline / 95 |
| Fuel standard | DIN EN 228 (gasoline) |
| Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A) | 74.6 / - / 69 |
| Consumption / emissions* | |
| Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>) | 6.3 - 6.2 (37.3 - 37.9) / 4.3 - 4.0 (54.7 - 58.8) / 5.1 - 4.8 (46.1 - 49.0) |
| CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>) | 116 - 111 (186.7 - 178.6) |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 <i>mi</i>) / 2 years, whichever comes first |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 14 / 20 / 21 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1280 (2821.9) / 1355 (2987.3) / 1830 (4034.5) |
| Front/rear axle load limit in kg (<i>lb</i>) | 965 (2127.5) / 960 (2116.4) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1700 (3747.9) / 1500 (3306.9) // 670 (1477.1) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 (165.3) / 80 (176.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 10 (2.6) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 4.3 (4.5) |
| Fuel tank capacity in liters (<i>US gal</i>) | 50 (13.2) |
| Dimensions / body | |
| Body type / number of doors | Unitary steel / 5 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.29 / 2.17 (23.4) |
| Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (<i>ft</i>) | 4343 (14.2) / 1816 (6.0) / 1449 (4.8) |
| Width including mirrors in mm (<i>ft</i>) | 1984 (6.5) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2636 (8.6) / 1554 (5.1) / 1525 (5.0) |
| Height of loading edge with steel springs in mm (<i>ft</i>) | 671 (2.2) |
| Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1200 (42.4) |
| Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>) | 380 (13.4) |

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

| Technical Data | Audi A3 Sportback 35 TDI S tronic (110 kW) |
|--|--|
| Program for Germany | Status: 03/06/2020 |
| Engine / electrics | |
| Engine type | Inline 4-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1968 / 81.0 x 95.5 / 16.0 |
| Max. power output in kW (PS) / rpm | 110 (150) / 3000 - 4200 |
| Max. torque in Nm (lb-ft) / at rpm | 360 (265.5) / 1600 - 2750 |
| Mixture preparation | Common rail fuel injection system, intercooler |
| Exhaust emission control | Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter |
| Emissions standard | Euro 6d-TEMP-EVAP-ISC |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 420 / 70 |
| Max. electrical output at 12V in kilowatts | 1.6 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | |
| Drive type | Front-wheel drive |
| Clutch | Two electrohydraulically controlled multi-plate clutches in an oil bath |
| Transmission type | 7-speed S tronic / dual clutch |
| Final drive ratio 1 to 2 | 4.167 |
| Final drive ratio 2 to 3 | 3.125 |
| Transmission ratio in 1st/2nd gear | 3.579 / 2.750 |
| Transmission ratio in 3rd/4th gear | 1.677 / 0.889 |
| Transmission ratio in 5th/6th gear | 0.677 / 0.722 |
| Transmission ratio in 7th/8th gear | 0.561 / - |
| Transmission ratio reverse gear | 2.9 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | Four-link rear suspension |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio | 14.9 |
| Turning circle in m (ft) | 11.1 (36.4) |
| Brake control system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist |
| Basic tires | 205/55 R 16 91 V |
| Wheels | Steel 7.0Jx16" |

| | |
|--|---|
| Performance / acoustics | |
| Top speed in km/h (<i>mph</i>) | 224 (139.2) |
| Limited | no |
| Acceleration, 0-100 km/h (0-62.1 <i>mph</i>) | 8.4 |
| Fuel type / octane value | Diesel / - |
| Fuel standard | DIN EN 590 (Diesel) |
| Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A) | 72.8 / - / 70 |
| Consumption / emissions* | |
| Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>) | 4.3 - 4.2 (54.7 - 56.0) / 3.7 - 3.5 (63.6 - 67.2) / 3.9 - 3.7 (60.3 - 63.6) |
| CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>) | 103 - 98 (165.8 - 157.7) |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 <i>mi</i>) / 2 years, whichever comes first |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 16 / 22 / 23 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1410 (3108.5) / 1485 (3273.9) / 1960 (4321.1) |
| Front/rear axle load limit in kg (<i>lb</i>) | 1090 (2403.0) / 965 (2127.5) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1800 (3968.3) / 1600 (3527.4) // 740 (1631.4) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 (165.3) / 80 (176.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 12.1 (3.2) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 5.5 (5.8) |
| Fuel tank capacity in liters (<i>US gal</i>) | 50 (13.2) |
| AdBlue fuel tank capacity in liters (<i>US gal</i>) | 12 (3.2) |
| Dimensions / body | |
| Body type / number of doors | Unitary steel / 5 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.28 / 2.17 (23.4) |
| Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (<i>ft</i>) | 4343 (14.2) / 1816 (6.0) / 1449 (4.8) |
| Width including mirrors in mm (<i>ft</i>) | 1984 (6.5) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2636 (8.6) / 1554 (5.1) / 1525 (5.0) |
| Height of loading edge with steel springs in mm (<i>ft</i>) | 671 (2.2) |
| Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1200 (42.4) |
| Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>) | 380 (13.4) |

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

| Technical Data | Audi A3 Sportback 30 TDI (85 kW) |
|---|--|
| Program for Germany | Status: 03/06/2020 |
| Engine / electrics | |
| Engine type | Inline 4-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1968 / 81.0 x 95.5 / 16.0 |
| Max. power output in kW (PS) / rpm | 85 (116) / 2750 - 4250 |
| Max. torque in Nm (lb-ft) / at rpm | 300 (221.3) / 1600 - 2500 |
| Mixture preparation | Common rail fuel injection system, intercooler |
| Exhaust emission control | Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter |
| Emissions standard | Euro 6d-TEMP-EVAP-ISC |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 420 / 70 |
| Max. electrical output at 12V in kilowatts | 1.6 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | |
| Drive type | Front-wheel drive |
| Clutch | Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel |
| Transmission type | 6-speed manual transmission / manual |
| Final drive ratio 1 to 2 | 3.238 |
| Final drive ratio 2 to 3 | 3.238 |
| Transmission ratio in 1st/2nd gear | 3.750 / 1.952 |
| Transmission ratio in 3rd/4th gear | 1.200 / 0.878 |
| Transmission ratio in 5th/6th gear | 0.711 / 0.604 |
| Transmission ratio reverse gear | 3.583 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | Torsion-beam rear axle |
| Steering ratio | 14.9 |
| Turning circle in m (ft) | 11.1 (36.4) |
| Brake control system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist |
| Basic tires | 205/55 R 16 91 V |
| Wheels | Steel 7.0Jx16" |

| | |
|--|---|
| Performance / acoustics | |
| Top speed in km/h (<i>mph</i>) | 206 (128.0) |
| Limited | no |
| Acceleration, 0-100 km/h (0-62.1 <i>mph</i>) | 10.1 |
| Fuel type / octane value | Diesel / - |
| Fuel standard | DIN EN 590 (Diesel) |
| Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A) | 69.1 / - / 70 |
| Consumption / emissions* | |
| Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>) | 4.1 - 3.9 (57.4 - 60.3) / 3.4 - 3.2 (69.2 - 73.5) / 3.6 - 3.5 (65.3 - 67.2) |
| CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>) | 96 - 92 (154.5 - 148.1) |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 <i>mi</i>) / 2 years, whichever comes first |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 17 / 21 / 23 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1345 (2965.2) / 1420 (3130.6) / 1905 (4199.8) |
| Front/rear axle load limit in kg (<i>lb</i>) | 1040 (2292.8) / 945 (2083.4) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1800 (3968.3) / 1500 (3306.9) // 710 (1565.3) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 (165.3) / 80 (176.4) |
| Capacities | |
| Cooling system capacity (incl. heating) in liters (<i>US gal</i>) | 11.8 (3.1) |
| Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>) | 5.5 (5.8) |
| Fuel tank capacity in liters (<i>US gal</i>) | 45 (11.9) |
| AdBlue fuel tank capacity in liters (<i>US gal</i>) | 13 (3.4) |
| Dimensions / body | |
| Body type / number of doors | Unitary steel / 5 |
| Number of seats | 5 |
| Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>) | 0.29 / 2.17 (23.4) |
| Standard dimensions (length / width excluding mirrors / height with steel springs) in mm (<i>ft</i>) | 4343 (14.2) / 1816 (6.0) / 1449 (4.8) |
| Width including mirrors in mm (<i>ft</i>) | 1984 (6.5) |
| Wheelbase / track width front/rear in mm (<i>ft</i>) | 2636 (8.6) / 1554 (5.1) / 1525 (5.0) |
| Height of loading edge with steel springs in mm (<i>ft</i>) | 671 (2.2) |
| Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>) | 1200 (42.4) |
| Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>) | 380 (13.4) |

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used