

Technical Data		Audi Q2 30 TDI (85 kW)
Program for Germany	Status: 12/07/2018	
Engine / electrics		
Engine type	Inline 4-cylinder engine	
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	1598 / 79.5 x 80.5 / 16.2	
Max. power output in kW (hp) / at rpm	85 (116) / 3250 - 4000	
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1750 - 3200	
Mixture preparation	Common rail fuel injection system, intercooler	
Exhaust emission control	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	420 / 70	
Max. electrical output at 12V in kilowatts	1.6	
Drivetrain / transmission		
Drive type	Front-wheel drive	
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel	
Transmission type	6-speed manual transmission / manual	
Transmission ratio in 1st/2nd gear	4.111 / 2.118	
Transmission ratio in 3rd/4th gear	1.360 / 0.971	
Transmission ratio in 5th/6th gear	0.733 / 0.592	
Reverse gear ratio / final drive ratio 1-2	4.000 / 3.389	
Suspension / steering / brakes		
Type and design of front-axle suspension	McPherson struts, front	
Type and design of rear-axle suspension	Compound link rear suspension	
Steering	Electromechanical steering with speed-dependent power assistance	
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -	
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic)	205/60 R 16 92 V not available	
Wheels (basic)	Steel 6.0Jx16"	
Performance / acoustics		
Top speed in km/h (mph)	197 (122.4)	
Acceleration, 0-100 km/h (0-62.1 mph)	10.3	
Fuel type / octane value	Diesel / -	
Fuel standard	EN590	
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	66.8 / 70 / 68	

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	5.6-5.4 (42.0-43.6) / 4.5-4.2 (52.3-56.0) / 4.9-4.6 (48.0-51.1)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	128-121 (206.0-194.7)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 20 / 23
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1345 (2965.2) / 1420 (3130.6) / 1930 (4254.9)
Front/rear axle load limit in kg (<i>lb</i>)	1045 (2303.8) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (3747.9) / 1500 (3306.9) // 710 (1565.3)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	12 (3.2)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4.7 (5.0)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Adblue fuel tank capacity in liters (<i>US gal</i>)	13 (3.4)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / -
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / -

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

Technical Data	Audi Q2 30 TDI S tronic (85 kW)
Program for Germany	Status: 12/07/2018
Engine / electrics	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1598 / 79.5 x 80.5 / 16.2
Max. power output in kW (hp) / at rpm	85 (116) / 3250 - 4000
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1750 - 3200
Mixture preparation	Common rail fuel injection system, intercooler
Exhaust emission control	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter
Emissions standard	EU6
Start-stop / REM	yes / yes
Battery in A / Ah	420 / 70
Max. electrical output at 12V in kilowatts	1.6
Drivetrain / transmission	
Drive type	Front-wheel drive
Clutch	Dual clutch
Transmission type	7-speed S tronic / dual clutch
Transmission ratio in 1st/2nd gear	3.500 / 2.087
Transmission ratio in 3rd/4th gear	1.343 / 0.933
Transmission ratio in 5th/6th gear	0.974 / 0.778
Transmission ratio in 7th/8th gear	0.653 / -
Reverse gear ratio / final drive ratio 1-2	3.722 / 4.800
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Compound link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	205/60 R 16 92 V not available
Wheels (basic)	Steel 6.0Jx16"
Performance / acoustics	
Top speed in km/h (mph)	197 (122.4)
Acceleration, 0-100 km/h (0-62.1 mph)	10.5
Fuel type / octane value	Diesel / -
Fuel standard	EN590
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	66.8 / 69 / 68

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	5.3-4.9 (44.4-48.0) / 4.5-4.2 (52.3-56.0) / 4.8-4.5 (49.0-52.3)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	126-117 (202.8-188.3)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 20 / 23
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1360 (2998.3) / 1435 (3163.6) / 1945 (4288.0)
Front/rear axle load limit in kg (<i>lb</i>)	1065 (2347.9) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (3747.9) / 1500 (3306.9) // 710 (1565.3)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	12 (3.2)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4.7 (5.0)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Adblue fuel tank capacity in liters (<i>US gal</i>)	13 (3.4)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / -
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / -

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

Technical Data	Audi Q2 30 TFSI (85 kW)
Program for Germany	Status: 12/07/2018
Engine / electrics	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	999 / 74.5 x 76.4 / 10.5
Max. power output in kW (hp) / at rpm	85 (116) / 5000 - 5500
Max. torque in Nm (lb-ft) / at rpm	200 (147.5) / 2000 - 3500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor
Emissions standard	EU6
Start-stop / REM	yes / yes
Battery in A / Ah	320 / 59
Max. electrical output at 12V in kilowatts	1.3
On-board voltage 1 in volts	12
On-board voltage 2 in volts	-
Drivetrain / transmission	
Drive type	Front-wheel drive
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel
Transmission type	6-speed manual transmission / manual
Transmission ratio in 1st/2nd gear	3.769 / 1.955
Transmission ratio in 3rd/4th gear	1.281 / 0.973
Transmission ratio in 5th/6th gear	0.788 / 0.642
Reverse gear ratio / final drive ratio 1-2	3.182 / 4.353
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Compound link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	205/60 R 16 92 V
Wheels (basic)	Steel 6.0Jx16"
Performance / acoustics	
Top speed in km/h (mph)	197 (122.4)
Acceleration, 0-100 km/h (0-62.1 mph)	10.1
Fuel type / octane value	Gasoline / 95
Fuel standard	RON 95
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	70.0 / 67 / 66

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	6.3-6.1 (37.3-38.6) / 4.9-4.8 (48.0-49.0) / 5.4-5.2 (43.6-45.2)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	122-119 (196.3-191.5)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 19 / 21
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1225 (2700.7) / 1300 (2866.0) / 1800 (3968.3)
Front/rear axle load limit in kg (<i>lb</i>)	940 (2072.3) / -
Rear axle load limit min. / max. in kg (<i>lb</i>)	900 (1984.2) / 920 (2028.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1500 (3306.9) / 1300 (2866.0) // 650 (1433.0)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	10.6 (2.8)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4 (4.2)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Dimensions / body	
Body type / number of doors	- / 5
Number of seats	5
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / -
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / -

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

Technical Data	Audi Q2 30 TFSI S tronic (85 kW)
Program for Germany	Status: 12/07/2018
Engine / electrics	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	999 / 74.5 x 76.4 / 10.5
Max. power output in kW (hp) / at rpm	85 (116) / 5000 - 5500
Max. torque in Nm (lb-ft) / at rpm	200 (147.5) / 2000 - 3500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor
Emissions standard	EU6
Start-stop / REM	yes / yes
Battery in A / Ah	320 / 59
Max. electrical output at 12V in kilowatts	1.3
On-board voltage 1 in volts	12
On-board voltage 2 in volts	-
Drivetrain / transmission	
Drive type	Front-wheel drive
Clutch	Dual clutch
Transmission type	7-speed S tronic / dual clutch
Transmission ratio in 1st/2nd gear	3.765 / 2.273
Transmission ratio in 3rd/4th gear	1.531 / 1.133
Transmission ratio in 5th/6th gear	1.176 / 0.956
Transmission ratio in 7th/8th gear	0.795 / -
Reverse gear ratio / final drive ratio 1-2	4.170 / 4.778
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Compound link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	205/60 R 16 92 V
Wheels (basic)	Steel 6.0Jx16"
Performance / acoustics	
Top speed in km/h (mph)	197 (122.4)
Acceleration, 0-100 km/h (0-62.1 mph)	10.3
Fuel type / octane value	Gasoline / 95
Fuel standard	RON 95
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	70.0 / 68 / 66

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	6.1-5.9 (38.6-39.9) / 5.1-5.0 (46.1-47.0) / 5.4-5.3 (43.6-44.4)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	124-122 (199.6-196.3)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 19 / 21
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1250 (2755.8) / 1325 (2921.1) / 1830 (4034.5)
Front/rear axle load limit in kg (<i>lb</i>)	970 (2138.5) / -
Rear axle load limit min. / max. in kg (<i>lb</i>)	915 (2017.2) / 935 (2061.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1500 (3306.9) / 1300 (2866.0) // 660 (1455.1)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	10.6 (2.8)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4 (4.2)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.32 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / -
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / -

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

Technical Data		Audi Q2 35 TFSI (110 kW)	
Program for Germany		Status: 12/07/2018	
Engine / electrics			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1498 / 74.5 x 85.9 / 10.5		
Max. power output in kW (hp) / at rpm	110 (150) / 5000 - 6000		
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1500 - 3500		
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler		
Exhaust emission control	Catalytic converter, oxygen sensor		
Emissions standard	EU6		
Start-stop / REM	yes / yes		
Battery in A / Ah	320 / 59		
Max. electrical output at 12V in kilowatts	1.3		
Drivetrain / transmission			
Drive type	Front-wheel drive		
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel		
Transmission type	6-speed manual transmission / manual		
Transmission ratio in 1st/2nd gear	4.111 / 2.118		
Transmission ratio in 3rd/4th gear	1.360 / 1.029		
Transmission ratio in 5th/6th gear	0.857 / 0.733		
Reverse gear ratio / final drive ratio 1-2	4.000 / 3.647		
Suspension / steering / brakes			
Type and design of front-axle suspension	McPherson struts, front		
Type and design of rear-axle suspension	Compound link rear suspension		
Steering	Electromechanical steering with speed-dependent power assistance		
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic)	205/60 R 16 92 V		
Wheels (basic)	Steel 6.0Jx16"		
Performance / acoustics			
Top speed in km/h (mph)	212 (131.7)		
Acceleration, 0-100 km/h (0-62.1 mph)	8.5		
Fuel type / octane value	Gasoline / 95		
Fuel standard	DIN EN 228		
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	76.1 / 69 / 66		

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	7.3-7.0 (32.2-33.6) / 5.0-4.7 (47.0-50.0) / 5.9-5.5 (39.9-42.8)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	133-126 (214.0-202.8)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 20 / 21
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1265 (2788.8) / 1340 (2954.2) / 1860 (4100.6)
Front/rear axle load limit in kg (<i>lb</i>)	980 (2160.5) / 955 (2105.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (3747.9) / 1500 (3306.9) // 670 (1477.1)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	10.8 (2.9)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4.3 (4.5)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.31 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / not available
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / not available
Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>)	405 (14.3) / not available
Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>)	1050 (37.1)
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	405 (14.3)

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used

Technical Data		Audi Q2 35 TFSI S tronic (110 kW)	
Program for Germany		Status: 12/07/2018	
Engine / electrics			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1498 / 74.5 x 85.9 / 10.5		
Max. power output in kW (hp) / at rpm	110 (150) / 5000 - 6000		
Max. torque in Nm (lb-ft) / at rpm	250 (184.4) / 1500 - 3500		
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler		
Exhaust emission control	Catalytic converter, oxygen sensor		
Emissions standard	EU6		
Start-stop / REM	yes / yes		
Battery in A / Ah	320 / 59		
Max. electrical output at 12V in kilowatts	1.3		
Drivetrain / transmission			
Drive type	Front-wheel drive		
Clutch	Dual clutch		
Transmission type	7-speed S tronic / dual clutch		
Transmission ratio in 1st/2nd gear	3.500 / 2.087		
Transmission ratio in 3rd/4th gear	1.343 / 0.933		
Transmission ratio in 5th/6th gear	0.974 / 0.788		
Transmission ratio in 7th/8th gear	0.653 / -		
Reverse gear ratio / final drive ratio 1-2	3.722 / 4.800		
Suspension / steering / brakes			
Type and design of front-axle suspension	McPherson struts, front		
Type and design of rear-axle suspension	Compound link rear suspension		
Steering	Electromechanical steering with speed-dependent power assistance		
Turning circle / turning circle optional in m (ft)	11.1 (36.4) / -		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic)	205/60 R 16 92 V		
Wheels (basic)	Steel 6.0Jx16"		
Performance / acoustics			
Top speed in km/h (mph)	212 (131.7)		
Acceleration, 0-100 km/h (0-62.1 mph)	8.5		
Fuel type / octane value	Gasoline / 95		
Fuel standard	DIN EN 228		
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	76.1 / 69 / 65		

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	7.1-6.4 (33.1-36.8) / 4.8-4.5 (49.0-52.3) / 5.7-5.3 (41.3-44.4)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	129-119 (207.6-191.5)
Servicing / guarantee (Germany)	
Service interval (<i>mi</i>)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 20 / 21
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1290 (2844.0) / 1365 (3009.3) / 1880 (4144.7)
Front/rear axle load limit in kg (<i>lb</i>)	1005 (2215.6) / 955 (2105.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (3747.9) / 1500 (3306.9) // 680 (1499.1)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	10.8 (2.9)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	4.3 (4.5)
Fuel tank capacity in liters (<i>US gal</i>)	50 (13.2)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.31 / 2.29 (24.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4191 (13.7) / 1794 (5.9) / 1538 (5.0) / not available
Width including mirrors in mm (<i>ft</i>)	2009 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2601 (8.5) / 1547 (5.08) / 1541 (5.06)
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	740 (2.4) / not available
Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>)	405 (14.3) / not available
Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>)	1050 (37.1)
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	405 (14.3)

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used